



Wind Turbine Installation Vessel

VOLE AU VENT

VESSEL

Jack-up vessel, Category

Heavy Maintenance and Construction

Classification DNV GL № 1A1 Self-elevating Wind Turbine

Installation Unit SPS Crane Unit HELDK

CRANE OPP-F E0 DYNPOS-AUTR CLEAN

140.4 m (without Heli Deck)

Breadth 41 m

Maximum Draft

Moulded Depth

DWT 8,000 t

DP Class 2 Dynamic Positioning

CRANE AND JACK-UP SYSTEM

Liebherr CAL 45000-1200 Crane Make

1,500 t at 17 m Max. Lifting Capacity

133.9 t at 104 m

Aux. Hoist 100 t at 109.6 m (man-riding)

Cargo Deck 3,400 m²

Max. Deck Load

Max. Cargo Weight 6.500 t

Jack-up System Double ring for continuous jacking operation


Min. Water Depth 7 m

Max. Water Depth 50 m

Leg Length 90 m

4 x 124.5 m² Area of Spud Cans

The content of this document is provided strictly for information purposes only. Whilst it has been endeavoured to procure completeness and accuracy, no warranty - express or implied - is given, in particular of fitness for a particular purpose. In no event any Jan De Nul Group company will be liable for any whatsoever damages arising directly or indirectly from the use of or reliance on the content provided herein, even if (previous) advice has been given/received that such damages may occur.



MACHINERY - PROPULSION

Main Gen. Sets 6 x diesel engine 4,000 kW at 600 rpm,

3 x 6,600 V, 60 Hz

Emergency Gen. Set 1 x air-cooled 781 kW at 1,800 rpm

4 x azimuth thrusters 2.600 kW Main Propulsion

Bow Thrusters 3 x bow tunnel thrusters 2,500 kW

Transit Speed 10 kn

Max. Speed 12 kn

Max. endurance 30 days

ACCOMMODATION

Accommodation 90 persons

Heli Deck Yes, D=22.2 m,

> MTOW = 12.8 t for Sikorsky S92, Sikorsky S61N, Super Puma AS 332L2

BUILDING INFORMATION

Shipyard Crist Shipyard in Gdynia (Poland)

Delivered December 2013







